



























COLOR CODE	NAME-PART#-IMAGE	DESCRIPTION	I.D. SIZE	COLORS	PACKAGING
MARINE FUEL	 TRIDENT A2 CORRUGATED FUEL FILL - USCG•ISO•SAE•NMMA•LLOYD'S•CE 329 NEW	Trident corrugated A2 Marine Fuel Fill Hose is now Lloyd's Registry Type Approved. Exceeds ABYC H-24 & H-33, SAE J1527, ISO 7840 & USCG Type A2; and is NMMA Type Accepted & CE certified. Built with thick wall, corrugated cover, smooth tube and wire helix between 2 ply reinforcement for extra Bend-ability and service life. Formulated for max resistance to fire, heat, cold, ozone, aging, and permeation by all fuels including alcohol blends. Perfect for diesel fuel tank transfer hose.	In./mm 1-1/2" to 2-3/8" 38mm to 60mm	Black with Red Stripe	50' (15m) Coil 12.5' (3.8m) Length Boxed on request up to 1.5" (38mm)
	 TRIDENT A2 FUEL LINE & FILL - USCG•ISO•SAE•NMMA•LLOYD'S•CE 327 NEW	Trident A2 Marine Fuel Hose (Fill & Vent plus diesel Distribution, Return & Transfer) is now Lloyd's Registry Type Approved Cert. 02/00030. Exceeds ABYC H-24 & H-33, SAE J1527, ISO 7840 & USCG Type A2; and is NMMA Type Accepted and CE certified. Built with thick wall, smooth cover and tube, wire helix between 2 ply reinforcement for extra service life and Bend-ability. Formulated for max resistance to fire, heat, cold, ozone, aging, permeation by all marine fuels including alcohol blends.	3/4" to 2-3/8" 19mm to 60mm	Black with Red Stripe	50' (15m) Coil 12.5' (3.8m) Length Boxed on request up to 1.5" (38mm)
	 TRIDENT A1 FUEL LINE - USCG•ISO•SAE•NMMA•ABYC•CE 365	Trident Barrier Lined A1 Marine Fuel Hose (Distribution, Return, Vent and Transfer) for both (gasoline/petrol) and diesel (including alcohol blends). Exceeds ABYC H-24 & H-33, SAE J1527, ISO 7840 & USCG Type A1; and is NMMA Type Accepted and CE certified. Built with best fuel, fire and age resistant formulation, 2 spiral reinforcement and unique "Barrier Liner" on inside surface of tube so fuel is not in direct contact with rubber. Provides extraordinary resistance to fuel permeation and aging, as well as fire, heat, cold, and ozone. Also good Bend-ability.	1/4" to 5/8" 6.3mm to 16mm	Black	Reels: 475'-575'(145-175m) 250'(76m) Boxed: 100'(30.5m) 50'(15m) 25'(7.6 m)
	 TRIDENT B1 FUEL LINE - USCG•ISO•SAE•NMMA•ABYC•CE 309	Trident B1 Marine Fuel Hose (distribution and vent) for outboards. Meets ABYC H-24 & H-33, SAE J1527, ISO 8469, USCG Type B1; and is NMMA Type Accepted & CE certified. Fuel resistant thermo-plastic formulation with 2 spiral reinforcement provides excellent bendability and resistance to UV, aging and permeation by all marine fuels (gasoline/petrol and diesel) including alcohol blends.	1/4" to 5/8" 6.3mm to 16mm	Light Gray	Reels: 700'(213m) Boxed: 100'(30.5m) 50'(15m) 25'(7.6 m)
FITTINGS	 PARKER COMMERCIAL FUEL HOSE & FITTINGS-USCG A1•SAE J1942•ISO•CE 221R NEW SAE J1527•NMMA•ABYC•LLOYD'S•DNV•ABS	Type A1 Marine Fuel Hose for Commercial, Inspected & Recreational Vessels (Distribution, Return, Vent & Transfer) for gasoline, alcohol blends & diesel. Exceeds all USCG, SAE J1942 & 1527 A1, ABYC H24 & H33 Standards; CE Certified; Type Approved by NMMA, Lloyd's, DNV & ABS. Reinforced with 1 braid high tensile steel wire, blue (wipe clean) rubber cover & 2000psi burst pressure. Excellent flexibility. Resistant to all fuels, oil, weather, aging, abrasion, fire, heat, cold & ozone. Required on passenger vessels of 6 passengers or more. Uses Parker (Brass, Steel & Stainless Steel) reusable & crimp on fittings. Assembly and crimping equipment available.	1/4" to 5/8" 6.3mm to 21mm 5/16" 7.8mm 13/32" 10mm 1/2" 13mm 5/8" 16mm 7/8" 21mm	Blue	50' (15m) Boxed Bulk Reels: 350' to 150' (107m to 46m)
	 BRASS HOSE FITTINGS, FERRULES & ADAPTERS 500 - 600 - 700	Solid brass Standard Hose Fittings, Ferrules & Pipe Adapters stocked in all fuel hose sizes. Manual ferrule crimpers and dies are available. For complete detail, see our retail price list. To be used with 309 & 365 Series Fuel Hoses.	See retail price list	Brass	Bulk - 100 each Carton of 10 each
MARINE WET EXHAUST AND WATER	 STAINLESS STEEL T-BOLT EXHAUST CLAMPS & CONSTANT TORQUE CLAMPS 720 730	Trident T-Bolt Clamps: 3/4" (19mm) Wide, 316 Stainless Steel band & 18-8 Stainless Steel T-Bolt & Lock Nut (with nylon insert). Very strong and secure for critical applications. Constant Torque Clamps: All Stainless Steel 5/8" (16mm) wide band, liner, housing, screw and Belleville Springs. 7/8" (22mm) OD Range. Automatically expands and contracts to compensate for heat & cold.	5/8" to 18" 16mm to 457mm	Solid Stainless Steel	12/Bag As Required 25/Box
	 TRIDENT SILICONE & RUBBER WET EXHAUST ELBOWS & BELLOW (SAE J2006) 5-10 YEAR WARRANTY	Trident Silicone & Rubber Elbows & Hump Hose Bellows provide the ultimate flexible connectors for Marine Wet Exhaust Systems. They offer much greater tolerance to heat, misalignment, engine movement & vibration, with significant savings in cost, parts, labor and space. Highest max. continuous operating temps - Molded Black Hi Temp EPDM Rubber 250°F (121°C), Blue Very Hi Temp. Silicone 350°F (177°C), Red Xtra Hi Temp. Silicone 500°F (260°C). Silicone (Blue and Red), also available w/ 4 to 6 ply reinforcement. All exceed (SAE J2006-R3, and ABYC & NMMA P1) Std. See Marine Wet Exhaust Systems Catalog.**	1-1/2" to 18" 38mm to 457mm	Black Blue Brick Red	Bulk or boxed with 4 Stainless Steel T-bolt Clamps
	 TRIDENT SILICONE MARINE WET EXHAUST & WATER(SAE J2006) 202V/202X 10 YEAR WARRANTY	Trident Silicone Marine Wet Exhaust & Water-Coolant Hose is the ultimate in extra thick soft wall silicon quality with very high temp. performance and extra long service life. Exceeds SAE J2006-R1, and ABYC & NMMA P-1 exhaust standards. #202V Glossy Blue "Very Hi Temp" has 4-6 ply polyester reinforcement and 350°F (177°C) Max. #202X Glossy Red "Xtra Hi Temp" has 4 ply Nomex® reinforcement, and 500°F (260°C)Max.Used world wide on premium boats, yachts and special service vessels. It has become the super yacht standard. See-Trident Marine Wet Exhaust System Catalog.**	1" to 18" 25.4mm to 457mm	Glossy Blue with Red Tube or Brick Red	I.D. Lengths ALL 3'-6'-12' (0.9-1.8-3.7m) 1-5" 25' (25.4-127mm) (7.6m)
	 TRIDENT BLUE CORRA-SIL MARINE WET EXHAUST & WATER HOSE (SAE J2006) 252V 10 YEAR WARRANTY	Trident Blue Corra-sil Corrugated Silicone Marine Wet Exhaust & Water Coolant Hose is the ultimate in flexible exhaust quality with "Real Hat" VHT performance, extra long service life and excellent long length bendability. Exceeds SAE J2006-R2, and ABYC, & NMMA P-1 exhaust standards and black rubber exhaust features. Built with extra thick wall, glossy blue corrugated cover, smooth red tube, wire helix between 2 ply polyester reinforcement and 350°F (177°C) Max. Perfect for long, bent wet exhaust (genset and engine) run and premium raw water and coolant hose runs. See Marine Wet Exhaust Systems Catalog.**	3/4" to 18" 19mm to 457mm	Glossy Blue w/Red Tube	I.D. Lengths ALL 3'-6'-12' (0.9-1.8-3.7m) 3/4"-5" 25' (19-127m) (7.6m)
	 TRIDENT CORR MARINE WET EXHAUST HOSE (SAE J2006 & LLOYD'S) 5 YEAR WARRANTY	Trident corrugated marine wet exhaust hose for longer connections with substantial bends. Thick tube and cover with wire helix between 2 ply reinforcement. Exceptional flexibility and bend radius. Resists heat, ozone, exhaust fumes, panting and collapse. Exceeds (SAE J2006-R2, and ABYC & NMMA P-1 exhaust standards). New Lloyd's Registry Type Approved Cert. 02/00029. Black High Temp EDPM Rubber 250°F (120°C) Max.**	1-1/2" to 10" 38mm to 254mm	Black w/Blue Stripe	I.D. Lengths ALL 6.25'-12.5' (1.9-3.8m) 1"-6" Coils (25.4-152mm) 50' (15m)
	 TRIDENT FLEX MARINE WET EXHAUST & WATER (SAE J2006 & LLOYD'S) 250/100 5 YEAR WARRANTY	Trident Flex wet exhaust hose for longer bent connections. In smaller I.D.'s for engine intake, critical water, drain, scupper bilge & sanitation uses. Extra heavy tube and cover with wire helix between 2 ply reinforcement provides excellent flexibility and bend radius. Resists heat, ozone, exhaust, sani chemicals, panting and collapse. Exceeds (SAE J2006-R2, and ABYC & NMMA P-1 exhaust standards). New Lloyd's Registry Type Approved Cert. 02/00029. Black High Temp EDPM Rubber 250°F (120°C) Max.**	1/2" to 10" 13mm to 254mm	Black w/Blue Stripe	I.D. Lengths ALL 6.25'-12.5' (1.9-3.8m) Coils 1/2"-4" 5' (13-102mm) (15..)
	 TRIDENT PLY MARINE WET EXHAUST & WATER (SAE J2006 & LLOYD'S) 200/110 5 YEAR WARRANTY	Trident Ply marine wet exhaust hose for short, straight connections. In smaller I.D.'s for critical engine coolant & circulation, heat exchanger and discharge uses. Extra heavy tube and cover with 2 to 6 ply reinforcement resists heat, aging, ozone, exhaust and sani chemicals. Exceeds (SAE J2006-R1, and ABYC & NMMA P-1 exhaust standards). New Lloyd's Registry Type Approved Cert. 02/00029. Black High Temp EDPM Rubber 250°F (120°C) Max.**	1/2" to 10" 13mm to 254mm	Black w/Blue Stripe	I.D. Lengths ALL 6.25'-12.5' (1.9-3.8m) Coils 1/2"-2-1/2" 50' (13-63.5mm) (15m)



COLOR CODE	NAME-PART#-IMAGE	DESCRIPTION	I.D. SIZE	COLORS	PACKAGING	
MARI WATER	TRIDENT SILICONE & RUBBER HEATER HOSE (SAE J20R3) 130/131V  2/7 YEAR WARRANTY	131V Ultimate Silicone heater hose - Very Hi Temp Blue with Red Tube provides much greater Temp. range and service life than standard EPDM rubber #130 Heater Hose. Both are 2 spiral polyester reinforced with similar working pressure for engine coolant water, A/C and other mid-pressure water applications. 131V (VHT-Blue), 45 to 75 PSI (0.31 to 0.52 Mpa) WP 350°F (177°C) SAE J20R3, Class 1 & J20 P3. 7 Year Warranty #130 (Standard Black) 50 PSI (0.34 Mpa) W.P. 212°F (100°C) SAE J20R3. 2 Year Warranty	1/4" to 1" 1/2" to 3/4"	6.3mm to 25mm 13 to 19	Blue Cover Red Tube Black	300'-175' (90-53m) Coils 50'-25' (15-7.6m) Boxes 500'-450' (150-140m) Reels 50' (15m) Boxed
	TRIDENT H.D. & X.H.D. WATER/AIR HOSE (SAE J20R3) 132/134  2/3 YEAR WARRANTY	Cost effective, Hi Temp, EPDM rubber, polyester reinforced and exceeds SAE J20R3. Both are resistant to coolants, ozone, cold & heat; and serve a variety of boat and plant pressurized application (water & air delivery) #132 is 2 spiral, 200PSI (1.38Mpa) W.P. #134 has 4 spiral, heavy wall and better bend radius and working pressure. 300 PSI (2.1Mpa) W.P. Operating Temp. -40°F to 212°F (-40°C to 100°C) #134 serves below water line intake and discharge applications (A/C, Eng, San) etc.	1/4" to 1"	6.3mm to 25mm	Black	REELS 750'-250' (230-75m) Boxed 50' (15m)
	TRIDENT SANI SHIELD SANITATION HOSE 102/101  5 YEAR WARRANTY	Premium Sanitation Hose for all head & holding tank connections. Extra thick tube & cover is specially formulated Black or White EPDM Rubber for Max. Resistance to Odor Permeation and winterizing with antifreeze. With wire helix between 2 ply reinforcement this hose has excellent bend radius, flexibility, and fitting acceptance and retention. This makes for easy installations with no heat gun or lubricant necessary. It's Legendary odor-free performance is the best on the market. Self draining installations still recommended. Not for potable water. NOW AVAILABLE IN WHITE.	1" to 1-1/2" 1-7/8"	25.4mm to 38mm 48mm	Black or White w/Green Stripe	50' (15m) Coil 12.5' (3.8m) Length (Boxed on request)
SANITATION	TRIDENT ODOR SHIELD SANITATION HOSE 140  3 YEAR WARRANTY	Extra odor-resistant sanitation hose for all head and holding tank connections. This smooth light grey hose has a special thermoplastic formulation that exceeds the odor resistance of our popular 148 series. The hard PVC helix gives the same good flexibility and bend radius. No cuffs required. Not for potable water applications, or for exposure to alcohol, petrochemicals or solvents. Self draining installations are necessary for longest odor free service. Max. operating temps. +10° to +140°F (-12° to +60°C). Max working pressure 70 PSI (0.48 Mpa).	1" & 1-1/2"	25.4mm & 38mm	Very Light Grey	100' (30.5m) Coil 50' (15m) Boxed
	TRIDENT VAC X.H.D. SANITATION HOSE - FDA 148  3 YEAR WARRANTY	Extra heavy duty sanitation hose of smooth white vinyl. Specially compounded to provide resistance to odor permeation and (FDA) potable water fill. Also for critical bilge, drain scupper, live well, etc. Hard PVC helix gives good flexibility and bend radius. No cuffs required.* Don't use with alcohols, anti freeze, petro-chemicals or solvents. Self draining installations are necessary for odor free service. Operating temperatures +10° to +140° F (-12° to +60°C).	5/8" to 1-1/2"	16mm to 38mm	White	100' (30.5m) Coil 50' (15m) Coil 50' (15m) Boxed 25' (7.6m) Boxed
	TRIDENT CLEAR PVC TUBING- FDA 150  2 YEAR WARRANTY	Non-toxic FDA compounded PVC for many unpressurized, cool water uses like fresh water, drain and vent lines. Operating temperatures +20° to +150° F (-7° to +66°C). NOT RECOMMENDED FOR BELOW WATERLINE THRU-HULL CONNECTIONS.	1/4" to 1-1/2"	6.3mm to 38mm	Clear	Coils: 250' to 1" (76m-25mm) 100' to 1-1/2" (30.5m-38mm) Boxed: 100' (30.5m) 50' (15m) 25' (7.6m)
POT WATER	TRIDENT REINFORCED PVC - FDA 164/162  2 YEAR WARRANTY	Nylon reinforced. FDA compounded PVC for pressurized drinking water systems, etc. No taste or odor. #164 "Cold Water". Max W.P. depending on I.D. size @ 70°F (21°C): #162=175 PSI (1.21Mpa), #164=150 PSI (1.03 Mpa). Operating temperatures +20° to +150° F (-7° to +66°C). NOT RECOMMENDED FOR BELOW WATERLINE THRU-HULL CONNECTIONS.	3/8" to 1"	9.5mm to 25.4mm	#164 White with Blue Tracer #162 Clear with Blue & Red Tracer	250' (76m) Coil 50' (15m) Boxed 25' (7.6m) Boxed
	TRIDENT HD REINFORCED PVC - FDA 161  3 YEAR WARRANTY	Heavy duty non-toxic FDA compounded PVC with nylon reinforcement. For pressurized drinking water systems and many other uses. Resists odor, taste and up to 250 PSI/WP (depending on I.D. size) @ 70°F (21°C). For cold and hot tap water. Operating temperatures +20° to +150°F. (-7° to +66°C) Good flexibility and bend radius.*	1/4" to 1-1/2"	6.3mm to 38mm	Clear	250' to 1" (76m-25mm) Coil 100' to 1-1/2" (30.5m-38mm) Coil 50' (15m) Boxed
	TRIDENT VAC - H.D. BILGE & LIVE WELL HOSE 144  2 YEAR WARRANTY	Heavy duty bilge, drain and live well hose. Clear vinyl (see thru) corrugated with black hard PVC helix and smooth tube. Provides exceptional flexibility and bend radius. NOT RECOMMENDED FOR BELOW WATERLINE THRU-HULL CONNECTIONS. No cuffs required. Operating temperatures +10° to +140° F (-12° to +60°C).	5/8" & 1-1/2"	16mm to 38mm	Clear with Black Helix	100' (30.5m) Coil 50' (15m) Boxed
BILGE & LIVE WELL & DRAIN	TRIDENT VAC - X.H.D. BILGE & LIVE WELL HOSE 147  3 YEAR WARRANTY	Smooth extra heavy wall vinyl hose. All clear (see thru) with black helix. Excellent durability, flexibility & bend radius for XHD bilge, live well, drain, scupper lines, etc. No cuffs required. Operating temperatures +10° to +140° F (-12° to +60°C).	5/8" & 1-1/2"	16mm to 38mm	#147 Clear with Black Helix #149 Any color with Quantity Special Order	100' (30.5m) Coil 50' (15m) Boxed
	TRIDENT BILGE HOSE 120/121  1 YEAR WARRANTY	Extremely flexible and tough corrugated polyethylene hose for bilge intake and discharge. Cuffed every foot for clamping. Resists oily bilge and sea water. NOT RECOMMENDED FOR BELOW WATERLINE THRU-HULL CONNECTIONS. Operating temperatures -40° to +200° F (-40° to +93°C).	5/8" & 1-1/2"	16mm to 38mm	#120 White #121 Black	Bulk Box: 500' to 150' (152-46m) 50' & 100' (15m & 30m) Boxed
	TRIDENT WIRE HARNESS CONDUIT 128  1 YEAR WARRANTY	Corrugated Polypropylene Conduit Hose. Safe and easy to install for multi-wire harness, cable & hose routing (like transom to O/B engine), and other applications. New ABYC Electrical Standard E-11 applies to all boats with AC or DC systems. Slit or Unslit. Fire Retardant/Self Extinguishing Polypropylene. Meets UL 94 V-2 as per ABYC E-11.16.4.1.9.	1/4" to 2"	6.3mm to 51mm	Black or White w/ Blue Stripe	Bulk Box: 1000' to 150' (305-46m) 50' (15m) Boxed
VENT	TRIDENT PVC VENT DUCT 400/402/406  1 YEAR WARRANTY	Wire supported vinyl ducting resists weather, sunlight and ozone. Won't support flame. 400-402 - Stand. vent ducting 3 mil. 406 H.D. Vent ducting 6 mil. Operating temperatures 0° to +160°F (-18° to +71°C).	3" & 4"	76mm & 102mm	#400 White #402 Black #406 Black	50' (15m) Boxed






TRIDENT MARINE HOSE

* Below water line connections - recommend double clamping and sealing compound. **Wet exhaust hose connections - recommend double clamping with stainless steel T-bolt or Constant-Torque clamps. Nomex® is a Trademark of e.i. DuPont.

AEGIS MARINE
info@mmimarine.com



COLOR CODE	NAME-PART#-IMAGE	DESCRIPTION	I.D. SIZE	COLORS	PACKAGING
A/C DUCTING	TRIDENT POLYDUCT 481 NEW 	Trident Polyduct - The most flexible, crush proof and rugged blower duct hose for Heat, Ventilation and Air Conditioning* (HVAC). Heavy Duty polypropylene hose, reinforced with a flexible polypropylene rod helix. It has excellent flexibility & compressibility; and excellent resistance to crushing, flex fatigue, tearing, and moisture*. Stomp on it and it returns to shape without damage. Shove it thru tight openings and overheads and it delivers full air flow. Meets FMVSS 302 flame resistance, Temp. Range: -40°F to +225°F (-40°C to 107°C). *when insulated	In./mm 3" to 8" 76 to 203	Blue	50' (15m) Lengths Boxed
	TRIDENT INSULATED AIR CONDITIONING DUCT 470 - 471 2 YEAR WARRANTY 	Thermo-efficient insulated Heating & A/C Duct. Black CPE Core (bonded to coated wire helix) easily expands over fittings & supports thick blanket of fiberglass insulation. #470 has tough polyethylene cover for Double Air Seal. #471 has fiberglass reinforced metalized cover. Rated R-4.2. Operating temperatures (-20°F to +250°F) (-29°C to +121°C). Meets UL 181, NFPA 90A and 90B.	3" to 8" 76 to 203 4" to 8" 102 to 203	#470 Black #471 Silver	25' (7.6m) Lengths Boxed
STEERING	MARINE STEERING HOSE & FITTINGS MSH NEW 	Marine Steering Hose - 1000 PSI Working Pressure - Low Volumetric Expansion. Polymeric core tube, fiber braid reinforcement, abrasion resistant urethane cover. Black, non-perforated cover, all layers bonded for optimum kink resistance & flexibility. -40°F to +212°F (-40°C to +100°C) except limited to +135°F (+57°C) for synthetic hydraulic fluids & water based fluids. Uses MS Series Brass Swaged, Crimped On or Reusable Fittings.	5/16" & 3/8" 7.8mm & 9.5mm	Black	50' (15m) Boxed 100' (30.5m) Box 600' (183m) Bulk Reel

ONLY TRIDENT OFFERS YOU COMPLETE MARINE HOSE MERCHANDISING SYSTEMS

Self-Dispensing Hose Centers with up to 4 times more product in the same space



New Self-Dispensing Reclosable Reel Boxes With New Heavy Duty Reels

Hose dispenses smoothly and tangle-free. End of hose is readily available and visible. 5 box sizes for maximum shelf loading (average 10 boxes per shelf).

TRIDENT HOSE CENTER

This unique self dispensing "center" replaces obsolete flat boxes. Our vertical packaging allows greater display and easier handling. It's practical, and saves valuable space and time.

Your sales will multiply with our "centers" due to high visibility, greater selection, graphic labeling, and the self-service features.

Ask for complete "Hose Center" set-up with heavy duty rack which includes shelves, sign, hose clipper, tape measure, Hose & Application Charts.

Two rack sizes [4' x 6' (1.2m x 1.8m) & 4' x 4 1/2' (1.2m x 1.4m) to fit any store requirement. Plan-ograph assortments from 21 boxes to our 31 BOX "COASTAL" Center.

ONLY TRIDENT USES DESCRIPTIVE COLOR CODED "ICON" LABELING

Shows what you need to know about the hose including application - Color coded RED, BLUE, GREEN, or BLACK

ONLY TRIDENT GUARANTEES PRODUCT FOR UP TO 10 YEARS



LIMITED WARRANTY
WARRANTY-TRIDENT RUBBER INC. warrants its products to be free from defects in material and workmanship under conditions of normal use and service when installed and used in its proper application in accordance with all applicable state and local laws. This warranty shall be for the term of up to ten years from date of purchase according to our literature, on the date of purchase. These may be covered by a separate manufacturers warranty for a longer period. This warranty does not apply to products which have been damaged for any reason after leaving the control of TRIDENT RUBBER, including but not limited to damage caused by abuse, misuse, negligence, accident, modification, installation, alteration, repair, or excessive temperature or pressure. During the warranty period, if a product is found to be defective in material or workmanship, it will be replaced or repaired without charge if returned, with prior approval, in accordance with the following instructions: The product should be packed carefully and returned, postal charges prepaid to: TRIDENT RUBBER INC. A note should be included advising the nature of the malfunction. Damage to the product incurred during packing or shipping the product is not covered under this warranty. Proof of purchase must accompany return. The foregoing obligations state TRIDENT RUBBER'S entire and exclusive liability and the buyers exclusive remedy for any claim or damages in connection with the sale or furnishing of products or parts, their design, installation or operation. TRIDENT RUBBER IN NO EVENT WILL BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR BREACH OF ANY WARRANTIES, EXPRESS OR IMPLIED IN FACT OR BY LAW WHATSOEVER, AND ITS LIABILITY UNDER NO CIRCUMSTANCES WILL EXCEED THE PURCHASE PRICE FOR THE PRODUCT. LIABILITY OF TRIDENT RUBBER UNDER ANY WARRANTY WHICH MAY BE IMPLIED BY LAW, INCLUDING WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, IS LIMITED SOLELY TO THE PERIOD OF TIME SET FORTH IN THIS WARRANTY. This warranty is designed as a LIMITED WARRANTY under the provisions of applicable federal law. Some states do not allow limitation on how long an implied warranty lasts or do not allow exclusion or limitation of incidental or consequential damages. So the above limitations and exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.



TRIDENT RUBBER, INC.®

1-800-414-BOAT

Web: www.tridentmarine.com • Email: trident@tridentmarine.com

585 Plum Run Road • Canonsburg, PA 15317 • USA
Phone 1(724) 745-9311 • Fax 1(724) 745-1709

©TRI 2005
13TH INTL. EDITION



AEGIS MARINE
info@mmimarine.com

